DATA COMMUNICATION SYSTEM, TRANSMITTER AND COMMUNICATION TERMINAL

|		
Publication number:	JP2002359833 (A)	**Also published as:**
Publication date:	2002-12-13	
Inventor(s):	SHIMIZU HIROSHI; SOMEYA RYUICHI	EP1246417 (A2)
Applicant(s):	HITACHI LTD	US2002162111 (A1)
Classification:		KR20020076114 (A)
- international:	*H04N7/26; H04N7/08; H04N7/081; H04N7/16; H04N7/173; H04W28/14; H04W74/00;* **H04N7/26; H04N7/08; H04N7/081; H04N7/16; H04N7/173;** H04W28/02; H04W74/00; (IPC1-7): H04N7/173; H04N7/08; H04N7/081; H04N7/16; H04N7/24	CN1378352 (A)
- European:	H04N7/173B2	
Application number:	JP20020019341 20020129	
Priority number(s):	JP20020019341 20020129; JP20010089025 20010327	

Abstract of **JP 2002359833 (A)**

PROBLEM TO BE SOLVED: To provide a data communication system and a communication terminal capable of reading data, even when a data transfer speed is lowered and interruption takes place in a streaming reproduction mode. SOLUTION: This data communication system is provided with a transmitter and a communication terminal. The transmitter is provided with a means for storing a plurality of data, a means for receiving a transmission request for first data from the communication terminal and a transmitting means for transmitting the first data to the communication terminal, in response to the transmission request.; Also, the communication terminal is provided with a means for transmitting a transmission request for the first data to the transmitter, a data-receiving means for receiving the first data, a first storage means for storing the first data, a second storage means for storing second data different from the first data, a read means for reading data stored in the first or second storage means, a displaying means for displaying data read by the reading means and a control means for controlling the reading means, so as to read data from the first or second storage means, according to the capacity of the first data stored in the first storage means.